



National Park Service

UTAH-400/DATA RS-422 Data Router

UTAH-400/DATA

The UTAH-400/DATA Router is a 64-port RS-422 router designed to switch machine control Data in conjunction with with the audio/video signal routing layers of a UTAH-400 Digital Routing SwitcherSystem. Each 3RU frame carries a single switch card that serves 64 data ports. A high-speed data bus arrangement is provided to connect up to four frames together to form larger routers with up to 256 ports.

As with all other routers in the UTAH 400 family, dual power supplies are provided as standard equipment. The UTAH-400/DATA router is controlled by the same MX-bus control system as all other UTAH 400 family devices.



UTAH-400/DATA Features

- Compact 3RU Package
- 64 RS-422 Ports per Frame
- Up to 4 Frames can be connected together
- Automatic Port Configuration

UTAH-400/DATA



The I/O ports on the UTAH-400/DATA Router can be automatically configured by the control system to serve either Controller or Tributary devices. The configuration of any port can be dynamically changed by the control system to allow the switcher to seamlessly follow selections where a device's control port may change between Controller and Tributary modes depending on the operations being carried out by the device.

The UTAH-400/DATA Router's I/O Connections are carried on RJ-45 connectors for easy cabling using standard data networking cables. The connector pin-outs follow the normal pattern for two-pair wiring. RJ-45 to 9-Pin adapters are available to simplify connecting to devices with 9-pin serial ports.

For Further Information

Regarding any of our products please feel free to contact us using the information below.

www.utahscientific.com

sales@utsci.com

Phone: +1 (801) 575-8801

Fax: +1 (801) 537-3099

4750 Wiley Post Way -- Suite 150

Salt Lake City, Utah

84116