

HUBbox™ T1310-T1310-05

Dual Channel 3G-/HD-/SD-SDI Optical Transmitter for SMPTE 297-2006 video applications

Data Sheet



Description

Dual SDI to Optical Fiber converter supports 3G-/HD-/SD-SDI and DVB/ASI. Support data rates from 2Mbps to 3Gbps.

The HUBbox™ comes equipped with AutoSFP® functionality, similar to the XFD line. This technology makes the HUBbox™ extremely flexible. Simply by replacing the SFP it can easily be changed into a dual receiver, dual transmitter or a transceiver. We've also added dual BNCs per channel to the design, giving dual outputs or loop-through.

It is housed in a compact and rugged aluminium case ideally suited to both studio and portable applications.

The HUBbox™ is perfect for using with an XFD system where one or two signals are required remotely.

Part Number Options

Part Number	Temperature
HUBbox NV30-T1310-T1310-05	-4°F to +131°F (-20°C to +55°C)

Features

- AutoSFP® functionality
- Loop-through output with reclocked SDI
- Multi-rate reclocking with automatic rate detection and automatic bypass for non SDI data rates
- Automatic Cable Equalization
- LEDs display power and SDI lock status
- Locking DC jack
- Optical LC/PC connector
- Delivered with 1310nm Fabry-Perot laser
- Typical Link lengths at 2.97Gbps:
 - Up to 30km @ 9µm SMF
- Excellent performance with SDI-Checkfield test signal at SD-, HD- and 3G-SDI
- Use in conjunction with HUBbox™ NV30-R17-R17 or the XFD system for a complete fiber transmit/receive system

General Operating Conditions

Parameter	Minimum	Typical	Maximum	Unit
Operating temperature	-4		+131	°F
Supply voltage (Vcc)	11		27	V
Dimensions	2.5" x 3.3" x 1.2" (excluding connectors)			
Weight	0.76 lb (145g)			

Electrical Characteristics

Parameter	Minimum	Typical	Maximum	Unit
Supported standards:				
• SMPTE	292M-2008, 259M-2008, 297M-2006, 424M-2006			
• DVBAISI	EN50083-9			
• Laser safety	Class 1 21CFR and IEC60825-1			
Number of IN/OUT BNCs	2 (transmitter input or receiver output)			
Number of OUT BNC's	2 (transmitter loop-through or receiver output)			
Typical input cable length equalization	Up to 140m of Belden 1694A @ 2.97Gbps Up to 200m of Belden 1694A @1.485Gbps Up to 400m of Belden 1694A @270Mbps			
Output signal level	800mVp-p \pm 10%			
Connectors	BNC			
Impedance	75ohm			
Return loss	\geq 15 dB [5-1485 MHz], \geq 10dB [1485-2970MHz]			
LED Indicators	Power, SFP type and SDI lock			
Data rate	2		3000	Mbps

Transmitter Optical Characteristics

Parameter	Minimum	Typical	Maximum	Unit
Transmitting circuit fiber	Single Mode (9/125 μ m), Multi Mode compatible			
Light source	Fabry-Perot laser			
Optical output power	-6	-2	-0	dBm
Optical extinction ratio	5			dB
Optical center wavelength	1290	1310	1330	nm
Spectral line width		1.5	3	nm
Optical rise/fall time (20-80%)		115	135	ps
Typical link length with 9 μ m SMF:				
@ 2.97 Gbit/s	10	30		km
@ 1.485 Gbit/s	20	30		km
@ 270 Mbit/s	30	30		km

All Rights Reserved. All trademarks are properties of their respective owners.
All prices and specifications are subject to change without notice.

Contact Us

Learn more at www.utahscientific.com



Email: info@utahscientific.com
Support: service@utahscientific.com
Sales: sales@utahscientific.com
Phone: 801.575.8801

Utah Scientific
 4750 Wiley Post Way, Suite 200
 Salt Lake City, Utah, 84116, USA
 U.S. and Canada Toll Free: 800.453.8782